



Features

The best communication interface, user friendly controls allow you to operate your monitor easily so you can devote your full attention to the fabulous images on screen.

Mouse and keyboard free, your fingers directly, easy to use for POS display, information board, industrial field, medical and transportation.

The stable removable base is engineered for the physical demands of touch screen use. The sturdy design helps foster intuitive operator entry and flexibility with a variety of applications to help reduce training time and costs and operational errors and

Panel	Cell Type / Glass Surface		TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size		5:4 / 19" viewable diagonal area
	Active Area / Pixel Pitch		376.3((H)x 301.1(V))mm / 0.294(H)x0.294(V)mm
	Native Resolution / Colors		1280(H)x1024(V)/ 16.7 Million
	Brighness / Contrast		250 cd/m ² (typ) / 800:1
	Response Time		≤5ms
	Viewing Angle		H.170°(-85°~+85°), V.160°(-80°~+80°)
	Light Source		CCFL, Long life, 50,000 hrs(typ)
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
		Sync	Composite Sync, Separate Sync, Sync On Green
		Frequency	F _h : 30 - 82Khz , F _v : 50 - 75Hz
	Audio System		2W Speaker X 2
Input Terminals	1 X VGA (15pin Female D-sub), 1 X PC Audio (Stereo Headphone Jack), 1 X DC Power Plug)		
Convenient Feature	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI,DDC 2B)		
	OSD Multi-Languages, Wall Mount Ready (VESA 75x 75mm)		
Power	External AC to 12VDC power adapter with universal / Auto sensig, AC 90 to 260V, 50/ 60 Hz		
Power Consumption	Operation / Power Saving	32 watt, < 2 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F), 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F),10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	With Base : (W x H x D): 412.3 X 345.4 X 209.7mm	
		Without Base : (W x H x D) 412.3 x 350.7 x 49.7 mm	
	Carton	(W x H x D) 470 x 445 x 142 mm	
Weight	N.W. / G.W.	6.0 Kg / 7.0 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	816 / 1632 / NA (Sets, By Pallet)	

Options

Touch Panel	Resolution	Transparency	Linearity	Durability	Driver
Resistive touch	2048x2048	80%+/-3%	X≤1.0%, Y≤1.0%	35 Million Times	MS-OS, Linux, QNX
Capacitive touch	2048x2048	80%+/-2%	X≤1.0%, Y≤1.0%	200 Million Times	MS-OS, Linux, QNX