

Features

Modularize mechanical design provides flexible product configuration and easy maintenance

Optional build-in touch screen for interactive application

Optional panel with ultra high brightness and super dynamic contrast, along option with auto-brightness sensor offers application in day and night

VGA connector with optional AV,SV,AV-Looping



Panel	Cell Type / Glass Surface		TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ration / Size		Wide / 22" viewable diagonal area
	Active Area / Rixel Pitch		473.8(H) x 296.1(V) mm / 0.82(H) x 0.282(V) mm
	Native Resolution / Colors		1680(H) x 1050(V) / 16.7 Million
	Brighness / Contrast		250 cd/m ² (typ) / 1000:1
	Response Time		≤5ms (G-to-G)
	Viewing Angle		H.170°(-80°~+80°), V.170°(-80°~+80°)
	Light Source		LED backlight , Long life, 35,000 hrs(typ)
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
		Sync	Separate Sync, Composite Sync, Sync On Green
		Frequency	F _h : 30 - 82Khz , F _v : 50 -75Hz
	Audio System		2W speaker X 2
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power Plug		
Convenient Feature	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI,DDC 2B)		
	OSD Multi-Languages, Wall Mount Ready (VESA 400x 200mm)		
Power	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	24.7 watt, < 1 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F),10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	Please refer to Drawing	
	Carton	W x H x D = TBD	
Weight	N.W. / G.W.	9 Kgs / 10.5 Kgs	
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets, By pallet)	

Options

Touch Panel	Video / TV	Enhanced Panel	Others
Resistive touch	SV+AV	Panel with LED backlight	Digital Signage (stand alone)
Capacitive touch	SV + AV + AV Looping	High brightness panel	Networking Digital Singnage
SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
Infrared touch		Sunlight Readable	Light sensor
Protected Glass			Auto-Dimming

元祺科技股份有限公司

3G Technology Inc.

新北市蘆洲區光復路99巷5號1樓

Tel: +886 2 2847 4730 Fax:+ 886 2 2847 2011

1F., No.5, Ln. 99, Guangfu Rd., Luzhou Dist., New Taipei City 24755, Taiwan

www.3gi.com.tw

